

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A lancet device comprising:

(a) a lancet including a seamless member comprising:having

first and second sharpened tips; and

a body with a first end and a second end with a length in between, the bodyseamless member hollowed along a portion of its length, wherein first and second sharpened tips extend from the first end, the first and second sharpened tips spaced directly opposite each other on the seamless member and extending parallel to a longitudinal axis of the seamless member, and wherein the seamless member is itself sufficiently rigid to penetrate skin with the sharpened tips; and

(b) a lancet holder arranged and configured on the second end of the body of the lancet to move the lancet a penetration distance to penetrate the skin of a patient with the first and second sharpened tips, wherein the penetration distance is less than a length of the sharpened tips.

2. (Currently Amended) The lancet device as claimed in claim 1 wherein the body of the seamless member is in the form of a cylindrical tube.

3. (Currently Amended) A lancet device comprising:

a lancet comprising:including

a unitary stainless steel member having a first end and a second end with a length in between, the unitary stainless steel member hollowed along only a portion of the length; and, wherein

first and second ground surfaces extendingextend from the first end to at least partially define first and second sharpened tips with a gullet between the sharpened tips; and

a lancet holder arranged and configured on the second end of the lancet to move the lancet a penetration depth to penetrate the skin of a patient with the first and second sharpened tips, the penetration depth being less than a length of the gullet.

4. (Previously Presented) The lancet device as claimed in claim 3 wherein the unitary member is in the form of a cylindrical tube.

5. (Canceled)

6. (Previously Presented) The lancet device as claimed in claim 3 wherein each of the first and second ground surfaces is a planar surface.

7. (Previously Presented) The lancet device as claimed in claim 6 wherein each of the first and second ground surfaces is a single angle ground surface.

8. (Previously Presented) The lancet device as claimed in claim 7 wherein the first ground surface extends from a horizontal plane at an acute angle relative to a longitudinal axis, wherein the horizontal plane is defined by the longitudinal axis and a lateral axis.

9. (Previously Presented) The lancet device as claimed in claim 8 wherein the first and second ground surfaces mirror one another about the horizontal plane.

10. (Previously Presented) The lancet device as claimed in claim 9 wherein each of the first and second ground surfaces extends approximately 180 degrees about the longitudinal axis.

11-31. (canceled)

32. (Withdrawn) A lancet comprising:

- (a) a unitary member which is hollowed along at least a portion of its length, said unitary member including a first end and a second end,
- (b) wherein the first end of said unitary member is shaped to include first, second and third sharpened tips.

33. (Withdrawn) The lancet of claim 32 wherein said unitary member is seamless.

34. (Withdrawn) The lancet of claim 33 wherein said unitary member is in the form of a cylindrical tube.

35. (Withdrawn) The lancet of claim 34 wherein the first end of said unitary member includes first, second and third ground surfaces.

36. (Withdrawn) The lancet as claimed in claim 35 wherein said unitary member includes a longitudinal axis, a lateral axis, a vertical axis, a horizontal plane and a vertical plane.

37. (Withdrawn) The lancet as claimed in claim 36 wherein each of said first, second and third ground surfaces is a planar surface.

38. (Withdrawn) The lancet as claimed in claim 37 wherein each of said first, second and third ground surfaces is a single angle ground surface.

39. (Withdrawn) The lancet as claimed in claim 38 wherein said first ground surface extends from the horizontal plane at an acute angle relative to the longitudinal axis.

40. (Withdrawn) The lancet as claimed in claim 39 wherein each of said first, second and third ground surfaces extends approximately 120 degrees about the longitudinal axis.

41. (Withdrawn) The lancet as claimed in claim 40 wherein said first, second and third ground surfaces are spaced equidistantly apart from one another.

42.-53. (canceled)

54. (Withdrawn-Currently amended) TheA lancet device of claim 3 further comprising: a third ground surface,

\_\_\_\_ (a) ~~a unitary member including a first end, a second end and a longitudinal axis,~~  
\_\_\_\_ (b) ~~wherein the first end of said unitary member is shaped to include first, second and third ground surfaces which together at least partially define a single tip and first, second and third cutting edges.~~

55. (Withdrawn)The lancet of claim 54 wherein the first, second and third cutting edges are spaced approximately 120 degrees apart from one another about the longitudinal axis.

56-58. (canceled)

59. (Withdrawn-Currently amended) TheA lancet device of claim 3 further comprising: a third ground surface and a fourth ground surface,

\_\_\_\_ (a) ~~a unitary member including a first end, a second end and a longitudinal axis,~~  
\_\_\_\_ (b) ~~wherein the first end of said unitary member is shaped to include first, second, third and fourth ground surfaces which together at least partially define a single tip and first, second, third and forth cutting edges.~~

60. (Withdrawn) The lancet of claim 59 wherein the first, second, third and fourth cutting edges are spaced approximately 90 degrees apart from one another about the longitudinal axis.

61-62. (canceled)

63. (Currently amended) A lancet device comprising:

a lancet including:

a partially hollow body member having a circumference defined by an outer wall, the partially hollow body having a first end, a second end and a length therebetween; and, wherein the outer wall defines

a first ground surface and a second ground surface extending from the first end and, the first and second ground surfaces each forming a gullet that extends approximately 180 degrees about a longitudinal axis of the lancet forming at an intersection a first tip and a second tip at the first end, and wherein the outerwall is itself sufficiently rigid to draw fluid from a patient; and

a lancet holder arranged and configured on the second end of the lancet to move the lancet to a penetration depth to penetrate the skin of a patient with the first and second tips, the penetration depth being less than a length of the gullet measured along the longitudinal axis.

64. (Canceled)

65. (Previously Presented) The lancet device of claim 63, wherein the first tip and the second tip are separated by first and second ground surfaces.

Application No. 10/767,867  
Inventor(s): Damon H. DeHart  
Application Filed: January 29, 2004  
Response to Office Action mailed February 22, 2011

66. (Currently amended) The lancet device of claim 63 wherein the body-member is in the form of a cylindrical tube.

67. -69. (Canceled)